


Conductor connections and junctions

AV 8



Application
For the following material thicknesses:
Inox, TiZn, Cu an AL up to 5.5 mm

Characteristics
Connection set for sheet metal ≥ 0.5 mm, including 4 rivets for lightening current carrying connection. Set can be also assembled on coloured or PVC coated surfaces.
New: Riveting with hand pliers possible
New: Higher pull-out forces (H-Test)
New: The tightness is tested and guaranteed
New: The tightness compared to the old rivets has been improved (better surface pressure)
New: Tightness and H- certification guaranteed even after aging

Material
For the following material thicknesses:

Legend
Also available as a multipack
a) for the connection of 2 conductors

Article-Nr.	E-Number									
270.094.000		H	InoxA2	6 - 10					a)	10

Accessories										
 Multi-range blind rivets AV 81										
Article-Nr.	E-Number									
275.063.011	156 990 020	H	0.5 - 6.5	10	RAL 9006, silver	4.1			a)	70
275.063.012	156 990 030	H	0.5 - 6.5	10	RAL 8014, brown	4.1			b)	70

Technical Specifications: **AV 8**

Article No.	270.094.000
Approved class H / N (EN 62561-1)	H
Material	InoxA2
Wire diameter	6 - 10 mm
Type of fastening screws	Hexagon screw
Type of connector	Access-clip
Surface protection	unbehandelt
Mounting hole	4 mm
comment	a)
Commercial specification	
Customs number	85389000
country of origin	CH
Texte	
comment	a)

