

Conical coupler

RV156 Conical coupling



**Application**  
Tensioned and current-proofed Cu, Cu-Steel or Bz cables

**Characteristics**  
Service load min. 3 kN / max. 25 kN  
Breaking load of corpus min. 80 kN

**Material**  
Corpus CuNiSi / Collet AIBz

**Legend**  
1) Sealed

| Article-Nr. |          |       |    |       |     |  |      |   |
|-------------|----------|-------|----|-------|-----|--|------|---|
| 615.211.000 | F107/S70 | 10.75 | 70 | 12.75 | 107 |  | 0.69 | 1 |

Technical Specifications: **Conical coupling RV156**

|                               |                     |
|-------------------------------|---------------------|
| Article No.                   | 615.211.000         |
| <b>Rail product name</b>      | F107/S70            |
| <b>Catenary wire diameter</b> | 10.75 mm            |
| <b>Catenary wire section</b>  | 70 mm <sup>2</sup>  |
| <b>Contact wire diameter</b>  | 12.75 mm            |
| <b>Contact wire section</b>   | 107 mm <sup>2</sup> |
|                               |                     |
| <b>comment</b>                | 1                   |
| Commercial specification      |                     |
| <b>Customs number</b>         | 85359000            |
| <b>country of origin</b>      | CH                  |
| Texte                         |                     |
| <b>comment</b>                | 1                   |
| Logistic specification        |                     |
| <b>Kilo / piece</b>           | 0.69 kg             |