


Splice fittings

■ SK8-198 Splice fitting



**Application**  
Contact wire splice fitting for copper or copper alloy contact wire

**Characteristics**  
Torque 50 Nm

**Material**  
Clamping plates CuNiSi

| Article-Nr. |  |  |  |  |  |  |  |  |  |
|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--|--|--|--|-------------------------------------------------------------------------------------|
| 635.037.000 | 4.5 - 8.5                                                                         | - 193                                                                             | - 150                                                                             | - 161                                                                             |  |  |  |  | 1                                                                                   |

Technical Specifications: **Splice fitting SK8-198**

|                               |              |
|-------------------------------|--------------|
| Article No.                   | 635.037.000  |
| Starting torque               | 50 N·m       |
| Contact wire section Cu       | - 193 mm²    |
| Contact wire section CuMg 0.2 | - 150 mm²    |
| Contact wire section CuAg     | - 161 mm²    |
| Contact wire groove           | 4.5 - 8.5 mm |
| Commercial specification      |              |
| Customs number                | 85359000     |
| country of origin             | undefined    |
| Logistic specification        |              |
| Kilo / piece                  | 1 kg         |

