


Earthing strip clamps

PA 88 Earthing strip clamps



Characteristics
With connection terminal for longitudinal and transversal wiring.
For conductor cross sections min. 1x 2.5mm² max. 2x 25mm²
resp. 1x Ø 8mm.

Article-Nr.	E-Number									
260.054.000	156 942 150	InoxA2	3/8"-1"	17.5-33.7	max.8					10
260.050.000	156 942 020	InoxA2	3/8"-2"	17.5-60.3	max.8					10
260.051.000	156 942 080	InoxA2	max.4"	max.114	max.8					10
260.052.000	156 942 130	InoxA2	max.6"	max.165	max.8					10
260.053.000	156 942 160	InoxA2	max.15"	max.400	max.8					10
260.055.000	156 942 170	InoxA2	max.23"	max.606	max.8					10

Technical Specifications: **Earthing strip clamps PA 88**

	260.054.000	260.050.000	260.051.000	260.052.000
Material	InoxA2			
Wire diameter	max.8 mm			
Nominal width	3/8"-1" Zoll	3/8"-2" Zoll	max.4" Zoll	max.6" Zoll
Cross section of the connecting conductors	6 - 35 mm²			
Number of conductors	2			
External diameter	17.5-33.7 mm	17.5-60.3 mm	max.114 mm	max.165 mm
Clamping/chucking range	17.5 - 33.7 mm	17.5 - 60 mm	17.5 - 114 mm	17.5 - 165 mm
Surface protection	unbehandelt			
Commercial specification				
Customs number	85389000			
country of origin	CE			
Logistic specification				
VPE Weight	0.558 kg	0.625 kg	0.728 kg	0.78 kg

	260.053.000	260.055.000
Material	InoxA2	
Wire diameter	max.8 mm	
Nominal width	max.15" Zoll	max.23" Zoll
Cross section of the connecting conductors	6 - 35 mm²	
Number of conductors	2	
External diameter	max.400 mm	max.606 mm
Clamping/chucking range	17.5 - 400 mm	17.5 - 606 mm
Surface protection	unbehandelt	
Commercial specification		
Customs number	85389000	
country of origin	CE	
Logistic specification		
VPE Weight	1.246 kg	1.655 kg

