


Earthing strip clamps

■ PA 88 Earthing strip clamps



**Characteristics**  
With connection terminal for longitudinal and transversal wiring.  
For conductor cross sections min. 1x 2.5mm<sup>2</sup> max. 2x 25mm<sup>2</sup>  
resp. 1x Ø 8mm.

| Article-Nr. | E-Number    |  |  |  |  |  |  |  |  |  |
|-------------|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--|--|--|--|-------------------------------------------------------------------------------------|
| 260.055.000 | 156 942 170 | InoxA2                                                                            | max.23"                                                                           | max.606                                                                           | max.8                                                                             |  |  |  |  | 10                                                                                  |



Technical Specifications: **Earthing strip clamps PA 88**

|                                                   |                        |
|---------------------------------------------------|------------------------|
| Article No.                                       | 260.055.000            |
| <b>Material</b>                                   | InoxA2                 |
| <b>Wire diameter</b>                              | max.8                  |
| <b>Nominal width</b>                              | max.23"                |
| <b>Cross section of the connecting conductors</b> | 6 - 35 mm <sup>2</sup> |
| <b>Number of conductors</b>                       | 2                      |
| <b>External diameter</b>                          | max.606                |
| <b>Clamping/chucking range</b>                    | 17.5 - 606 mm          |
| <b>Surface protection</b>                         | unbehandelt            |
| Commercial specification                          |                        |
| <b>Customs number</b>                             | 85389000               |
| <b>country of origin</b>                          | CE                     |
| Logistic specification                            |                        |
| <b>VPE Weight</b>                                 | 1.655 kg               |

