



Interception components

FL 76 Flat roof lead through



**Characteristics**  
For blankets of bituminous, mastic concrete or synthetic material, tablet (340x340mm) with welded tube

**Content**  
Incl. 2 cross clamps FE 43

| Article-Nr. | E-Number    |  |  |  |  |  |  |  |  |  |
|-------------|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--|--|--|-------------------------------------------------------------------------------------|
| 220.818.726 | 156 940 440 | H                                                                                 | InoxA2                                                                            | 900                                                                               | 6 - 9                                                                             | 33                                                                                |  |  |  | 2                                                                                   |

Technical Specifications: Flat roof lead through FL 76

|                                   |                                    |
|-----------------------------------|------------------------------------|
|                                   | 220.818.726                        |
| Approved class H / N (EN 62561-1) | H                                  |
| Material                          | InoxA2                             |
| Height H                          | 900 mm                             |
| Wire diameter                     | 6 - 9 mm                           |
| Diameter D                        | 33 mm                              |
| Type of accessory                 | Dach-, Wand- und Erderdurchführung |
| Surface protection                | unbehandelt                        |
| Commercial specification          |                                    |
| Customs number                    | 85389000                           |
| country of origin                 | CH                                 |
| Logistic specification            |                                    |
| VPE Weight                        | 9.434 kg                           |

