

Forked collar sockets

■ GI50/40,B20

**Application**

Tensioned Cu, Cu-Steel, steel or Bz cables

Characteristics

Service load min. 3 kN / max. 25 kN

Min. breaking load of corpus

Material

Corpus stainless steel / Collet AlBz

Legend

1) All components stainless steel A4

2) With colour code

Article-Nr.	«N»	mm Ø	mm²	mm Ø	mm²			Kg	
610.073.001	S161	16.8	161					1.51	2
610.082.001	S185	17.5	185					1.51	2
610.069.001	S202	18.8	202					1.51	2
610.091.000	S240	21	240					1.51	
610.065.000	S242	21	242					1.51	1
610.089.000	FD120			12.9	120			1.4	
610.087.000	FD150			14.5	150			1.4	
610.000.016	FD150			15.5	150			1.51	
610.079.001	FD193			16.8	193			1.51	2

Technical Specifications: **GI50/40,B20**

	610.073.001	610.082.001	610.069.001	610.091.000
Rail product name	S161	S185	S202	S240
Catenary wire diameter	16.8 mm	17.5 mm	18.8 mm	21 mm
Catenary wire section	161 mm²	185 mm²	202 mm²	240 mm²
Contact wire diameter				
Contact wire section				
Commercial specification				
Customs number	85359000			0
country of origin	CH			undefined
Logistic specification				
Kilo / piece	1.51 kg			

	610.065.000	610.089.000	610.087.000	610.000.016
Rail product name	S242	FD120	FD150	
Catenary wire diameter	21 mm			
Catenary wire section	242 mm²			
Contact wire diameter		12.9 mm	14.5 mm	15.5 mm
Contact wire section		120 mm²	150 mm²	
Commercial specification				
Customs number	85359000			
country of origin	undefined	CH		
Logistic specification				
Kilo / piece	1.51 kg	1.4 kg		1.51 kg

	610.079.001
Rail product name	FD193
Catenary wire diameter	
Catenary wire section	
Contact wire diameter	16.8 mm
Contact wire section	193 mm²
Commercial specification	
Customs number	85359000
country of origin	CH
Logistic specification	
Kilo / piece	1.51 kg

