

Loop with cotter





FRL 2 Loop with cotter



**Application**  
For standard insulators and copper or bronze cables or wires

**Characteristics**  
Conductor attachment via captive corded cotter made of stainless steel, loop on the side for opening

**Material**  
Inox A2 body, copper sling

| Article-Nr. | E-Number    |  |  |  |  |  |  |  |  |  |
|-------------|-------------|---|---|---|--|--|--|--|--|---|
| 111.057.102 | 156 252 070 | InoxA2  |   | 50  |  |  |  |  |  | 25  |



Technical Specifications: **Loop with cotter FRL 2**

|  |                    |
|--|--------------------|
| Article No.                                | 111.057.102        |
| Material                                   | InoxA2             |
| Nominal cross section conductor            | 50 mm <sup>2</sup> |
| For pull protected connections             | Yes                |
| Suitable for round conductors              | Yes                |
| Sleeve form                                | Short              |
| Suitable for high temperatures (to 650 °C) | No                 |
| Oil stop/centre bar                        | No                 |
| Suitable for fine strand conductors        | No                 |
| Type of connection                         | End connector      |
| Suitable for insulated varnish             | No                 |
| Insulation                                 | None               |
| Surface protection                         | blank              |
| Useful for stranded conductors             | Yes                |
| Voltage level                              | Up to 35kV         |
| Suitable for flat conductors               | No                 |
| Suitable for solid cores                   | No                 |
| Model                                      | Standard version   |
| Number of branches                         | 1                  |
| Commercial specification                   |                    |
| Customs number                             | 85359000           |
| country of origin                          | CH                 |
| Logistic specification                     |                    |
| VPE Weight                                 | 9.265 kg           |

