

Cable droppers

■ **SHTF1,2/10V** Non- current feeding, adjustable



**Application**  
For cable droppers, non-current feeding

**Characteristics**  
Other lengths and contact wire grooves on request

**Material**  
Clamp and adjustable part CuNiSi / Wire Bz 2

| Article-Nr. |  |  |  |  |  |  |  |  |  |
|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--|-------------------------------------------------------------------------------------|
| 625.117.577 | 12.5 - 17.5                                                                       | 95 - 185                                                                          | 3.75 - 8.5                                                                        | 250 - 600                                                                         | 4.5                                                                               | 10                                                                                  | 1.3                                                                                 |  | 0.462                                                                               |

Technical Specifications: **Non- current feeding, adjustable SHTF1,2/10V**

|                          |                |
|--------------------------|----------------|
| Article No.              | 625.117.577    |
| Length a                 | 250 - 600 mm   |
| Catenary wire diameter   | 12.5 - 17.5 mm |
| Catenary wire section    | 95 - 185 mm²   |
| Contact wire groove      | 3.75 - 8.5 mm  |
| Dropper wire diameter    | 4.5 mm         |
| Dropper wire section     | 10 mm²         |
| Slipping force           | 1.3 kN         |
| Commercial specification |                |
| Customs number           | 85359000       |
| country of origin        | CH             |
| Logistic specification   |                |
| Kilo / piece             | 0.462 kg       |

