


Photovoltaics

■ DS 50 PV Photovoltaics surge protection



- Characteristics**
- Surge protector photovoltaic type 2
 - limp = 5kA/pole (10/350
 - International disconnection, status indicator
 - follow and operating current: none
 - remote signaling

Article-Nr.	E-Number	 Typ/Type	 Yes	 kA I _{max}	 V U _C	 ns t _A	 kV U _P	 kA i _n		
296.480.391	808 486 320	T2	Yes	40	≤1200VDC	0	2.6	15		1

Technical Specifications: Photovoltaics surge protection DS 50 PV

Article No.	296.480.391
SPD type	T2
Number of poles	2
max. discharge current (Imax)	40 kA
Nominal discharge surge current (8/20)	15 kA
Voltage protection level [Up]	2.6 kV
Response time [ta]	0
Short circuit resistance (Icw)	1 kA
Follow current [IF]	0 kA
Fault indication	mechanisch, Rot
Temperature range	-40 - 85 °C
Material housing	Thermoplastik PEI UL-94-V0
Signaling on the device	Optic
Signaling contact	Yes
Connection cross section solid / stranded max.	1.5 mm²
Switching capacity signaling contact	250 V/0,5 A (AC) / - 30 V / 2 A (DC)
Energetically coordinated protective effect to the terminal	Yes
Exhausting	No
Operation voltage max. [Uc]	≤1200VDC
Nominal voltage DC	1000 V
Mounting method	DIN rail (top hat rail) 35 mm
Construction size	3 modular spacing
System configuration DC	Yes
Integrated backup fuse	No
Nominal discharge current [In]	15/Pol
Total discharge current (8/20) (L N-PE)	60 kA
Connection cross section	2 - 25 mm²
Degree of protection (IP)	IP20
Standards	
Test standards USA	UL 1449 ed.3
Test standards Europe	EN 50539-11
Test standards France	UTE C61-740-51
Commercial specification	
Customs number	85363000
country of origin	undefined