



Photovoltaics

■ DS 50 VGPVS Photovoltaics surge protection



- Characteristics**
- Surge protector photovoltaic type 1+2
 - 10 years warranty
 - $I_{imp} = 5\text{kA/pole (10/350)}$
 - internal disconnection, status indicator
 - follow and operating current: none
 - remote signaling



Article-Nr.	E-Number	Typ/Type		kA I_{imp}	kA I_{max}	V U_C	ns t_A	kV U_P	mm ²	
296.482.313	808 486 410	T1 / T2	Yes	6.25	40	≤1200VDC	0	2.8	2.5 - 25	1

Technical Specifications: Photovoltaics surge protection DS 50 VGPVS

Article No.	296.482.313
SPD type	T1 / T2
Number of poles	2
max. discharge current (Imax)	40 kA
Impulse current [Iimp]_(10/350)	6.25 kA
Discharge current max. (8/20) µs [Imax]	60 kA
Voltage protection level [Up]	2.8 kV
Operating current [Ic]	0 kA
Follow current [IF]	0 kA
follow current extinguishing capability [Ifi]	Unendlich
Response time [ta]	0
Short circuit resistance (Icw)	15 kA
Fault indication	mechanisch, Rot
Temperature range	-40 - 85 °C
Material housing	Thermoplastik PEI UL-94-V0
Signaling on the device	Optic
Signaling contact	Yes
Connection cross section solid / stranded max.	1.5 mm²
Switching capacity signaling contact	250 V / 0,5 A (AC) - 30 V / 2 A (DC)
Energetically coordinated protective effect to the terminal	Yes
Exhausting	No
Operation voltage max. [Uc]	≤1200VDC
Nominal voltage DC	1000 V
Mounting method	DIN rail (top hat rail) 35 mm
Nominal cross section conductor	2.5 - 25 mm²
Construction size	3 modular spacing
System configuration DC	Yes
Integrated backup fuse	No
Nominal discharge current [In]	15/Pol
Degree of protection (IP)	IP20
Standards	
Homologation	VDE, ÖVE und UL
Test standards USA	UL 1449 ed.3
Test standards Europe	EN 50539-11
Test standards France	UTE C61-740-51
Commercial specification	
Customs number	85363000
country of origin	undefined

