

Earthing bars

■ PES1350 / PES1630 Polygonal earthing bar

**Application**

Locate of earthing clamp to contact wire for temporary earthing of overhead lines.

Characteristics

The quick release coupling has easy locking for pivot according to DIN48087

Material

Polygonal tube out of glass fibre, foam filled top tube

Legend

1) PES1350

2) PES1630

Article-Nr.	mm a							Kg	
645.210.000	1350 - 3950							2.8	1
645.001.098	1630 - 5120							3	2

Accessories

Earthing wire guide 649.001.143

Article-Nr.								Kg	
649.001.143									0.385

Accessories

Signal flag 640.055.000

Article-Nr.	mm							Kg	
640.055.000	44								2

Accessories

Signalflag without fixing 649.002.000

Article-Nr.	mm							Kg	
649.002.000	44								3

Accessories

Bag 649.001.130

Article-Nr.								Kg	
649.001.130									0.8

Accessories



Bag 649.001.131

Article-Nr.									
649.001.131									0.5



Technical Specifications: **Polygonal earthing bar PES1350 / PES1630**

	645.210.000	645.001.098
Length a	1350 - 3950 mm	1630 - 5120 mm
Commercial specification		
Customs number	85359000	
country of origin	CH	
Logistic specification		
Kilo / piece	2.8 kg	3 kg

