

Supports 20mm

■ SP 20 KL Support



Application
1 cartridge Fischer Injection Mortar is sufficient for approx. 15 supports Ø20mm
1 cartridge of Sormat injection mortar is sufficient for approx. 9 supports Ø20mm

Characteristics
Support Ø 20mm made of Inox A2 for the modular assembly M16 of anchorage point and middle supports of cable system for glued assembly in concrete
assembly with superbond mortar FIS SB 390 S

Article-Nr.	E-Number									
310.503.002		InoxA2	500	20	4					1
310.603.001		InoxA2	600	20	4					1
310.703.001		InoxA2	700	20	4					1
310.803.001		InoxA2	800	20	4					1
310.903.001		InoxA2	900	20	4					1

Technical Specifications: **Support SP 20 KL**

	310.503.002	310.603.001	310.703.001	310.803.001
Material	InoxA2			
External diameter	20 mm			
Height H	500 mm	600 mm	700 mm	800 mm
Thread size anchorage point	M16			
Thread size basement	M20			
Number of person	4			
Commercial specification				
Customs number	73089000			
country of origin	CH			
	310.903.001			
Material	InoxA2			
External diameter	20 mm			
Height H	900 mm			
Thread size anchorage point	M16			
Thread size basement	M20			
Number of person	4			
Commercial specification				
Customs number	73089000			
country of origin	CH			

